

# Specifications

备注 (Remark)

1. 材料 (MATERIAL)

胶芯: PA6T/PBT+30%G.F UL94V-0, 颜色: 黑色.

Housing: PA6T/PBT+30%G.F UL94V-0, Color: Black

端子: 磷/青铜, 镍底30u"MIN, 表面镀金1u"MIN

Contact: Phosphor bronze, 1u"MIN GOLD PLATING OVER ALL

30u" MIN NICKEL UNDERPLATING OVER ALL

2. 特性 (characteristics):

额定电流: 3 AMP

Rating Current: 3 AMP.

接触阻抗: 20 mΩ MAX.

Contact Resistance: 20 mΩ MAX.

绝缘阻抗: 1000 MΩ MIN.


Insulating Resistance: 1000 MΩ MIN.

耐电压: AC 500V.

Withstanding Voltage: AC 500V.

温度范围: -40°C to +105°C




Temperture Range: -40°C to +105°C



# Ordering Information

F134-11 XX XX X RU AX

NO. OF PINS PER ROW 2-40P	Contact Plating	INSULATOR MATERIAL:	PACKING
	Full Of Gold	Semi-gold	A: PE Bag
	A0=0.8u"	B0=0.8U"	B: Tape & Reel
	A1=1u"	B1=1U"	C: Tube
	A2=1.5u"	B2=1.5U"	D: Tube+CAP
	A3=2u"	B3=2U"	E: Tray
	A4=3u"	B4=3U"	
	A5=5u"	B5=5U"	
	A6=10u"	B6=10U"	
	A7=15u"	B7=15U"	
	A8=20u"	B8=20U"	
	A9=30u"	B9=30U"	
	S1=Ordinary Tin Plated		
	S2=Matte Tin Plated		
	S3=Tin-plated High-temperature		



				OPERATION		SCALE		Fit		上海高霖电子有限公司		
				X.X	±0.40	UNIT		MM				
				X.XX	±0.25	SIZE	A4	DESIGN	卢小强	PART NO.	F134-11XXXXXRUX1	
				X.XXX	±0.15	SHEET	1/1	CHECK		TITLE:	2.54mm 单排母 塑高3.4 90度 U型 侧插	
REV	DATE	MODIFICATION DESCRIPTION	CHANGE	APPROVE	Angle	±3°	PROJ.	⊕	APPROVE	Customer No.		